



版次 (Version)	变更内容 (Rev. Content)	变更者 (Change Person)

技术参数 (Technical Data)		
项 目 (Item)	UL	IEC
额定电气参数 (Rated Electrical Parameters)	300V/2A	400V/5A
压线范围 (Wire Range)	24~20AWG	0.75mm ²
工频耐压 (Frequency Voltage)	AC 2000V	
冲击耐压 (Rated Surge Voltage)	4000V	
绝缘阻抗 (Insulation Resistance)	DC500V 500MΩ above	
接触电阻 (Contact Resistance)	≤20mΩ	
剥线长度 (Stripping Length)	9mm	
工作温度 (Temperature)	-40°C~+105°C	
材质和电镀 (Material and plating)		
绝缘材质 (Housing)	PA66 (UL94 V-0)	
触点材料 (Contact)	铜合金, 镀锡 (Copper alloy, Sn plated)	
弹片 (Spring)	/	

产品命名编码:
(Product Number Code):
GSL002A-3.5-XXP-1Y-00A (H)

产品型号 (Series No.) | 客户需求 (Customer Request)
极数 (No. of poles) | 塑体颜色 (Housing Color)

1: 单间距 (Single Pitch)	7: 透明色 (Transparent)
2: 双间距 (Double Pitch)	8: 白色 (White)
	9: 黄色 (Yellow)
	Y: 多种颜色 (Mixed Color)
	6: 红色 (Red)

P=3.50mm, N为孔位数 (N for hole digits), 有效位数为 (Significant Digits): 01P~XXP

N	01P	02P	03P	04P	05P	06P	07P
L	5.00	8.50	12.00	15.50	19.00	22.50	26.00
B	/	3.50	7.00	10.50	14.00	17.50	21.00
N	14P	15P	16P	17P	18P	19P	20P
L	50.50	54.00	57.50	61.00	64.50	68.00	71.50
B	45.50	49.00	52.50	56.00	59.50	63.00	66.50
N	08P	09P	10P	11P	12P	13P	
L	29.50	33.00	36.50	40.00	43.50	47.00	
B	24.50	28.00	31.50	35.00	38.50	42.00	
N	21P	22P	23P	24P	25P	...	
L	75.00	78.50	82.00	85.50	89.00		
B	70.00	73.50	77.00	80.50	84.00		

GOOSVN 宁波高胜电子有限公司
NINGBO GOOSVN ELECTRONIC CO.,LTD

型号 (Type): **GSL002A-3.5-XXP-1Y-00A (H)**

核准 (Approval): _____ 图号 (Drawing NO.): _____

审核 (Audit): _____ 单位 (Units): mm 页码 (Page): 1/1

设计 (Design): _____ 比例 (Scale): FULL

公差范围 (Tolerance Range):
150~ ±1.50
60~150 ±1.00
30~60 ±0.60
6~30 ±0.40
0~6 ±0.25

角度 (Angle): X ±2°
XX ±1°

版次 (Version): T0